

POWER TAKE-OFF GENERATORS

Generac's PTO line of generators offers dependable power at affordable prices. The 25,000, 40,000 and 60,000 watt models are Generac's answer to power failures. All three generators feature:

- Solid-state frequency compensation and voltage
- A rugged, dependable gear drive
- Sheet metal enclosure
- Easy-access control panel



GENERAC[®]
POWER SYSTEMS



PTO-25



PTO-40



PTO-60

- **Solid-State Frequency Compensated 1% V/F Voltage Regulation**
for fast response to changing load conditions and maximum motor starting power
- **Dependable Gear Drive**
eliminates breaking and stretching problems associated with unreliable chain drives
- **Sheet Metal Enclosure**
rust and rodent proof with a baked enamel finish
- **Control Panel**
rear-facing for easy monitoring from the tractor seat
- **Quick Disconnect**
- **Greater Surge Power**
- **Voltmeter Visible to Shaft Side**
- **Compact Design**

| Model | PTO-25 | PTO-40 | PTO-60 |
|--------------------------|--------------|--------------|----------------------|
| Model Number | 9738 | 9739 | 9740 |
| Rated Power (Continuous) | 25 kW-1Ø | 40 kW-1Ø | 60 kW-3Ø 54 kW-1Ø |
| Surge Power | 50 kW | 80 kW | 120 kW |
| Rated AC Amps at 240V | 104 | 166 | 180-3Ø 225-1Ø |
| Power Factor | 1.00 | 1.00 | .80-3Ø 1.00-1Ø |
| HP Required | 45 | 69 | 105 |
| PTO RPM | 540 | 540 | 1000 |
| Generator RPM | 1800 | 1800 | 1800 |
| Max. G Motor Starting † | 8 HP | 13 HP | 20 HP |
| Dimensions L"xW"xH" | 38 x 27 x 26 | 38 x 27 x 26 | 42 x 27 x 26 |
| Weight (lbs.) | 577 | 653 | 719 |

1Ø: Single Phase
 3Ø: Three Phase
 †: 30% Voltage Dip

- Units are mouse-proof when knock-outs are in place or when knock-out holes are re-covered
- To obtain full alternator capacity, electrical equipment must be permanently wired directly to the alternator or connected through the Quick Disconnect outlet
- Optional accessories (not included): PTO shaft kit and PTO trailer

DISTRIBUTOR

GENERAC[®]
 POWER SYSTEMS, INC.

P.O. BOX 8 • WAUKESHA, WISCONSIN 53187
 414/544-4811 • Fax: 414/544-0770