



LOAD BANK WIRING COLOR CODED AS FOLLOWS:  
 ALL AC CONTROL WIRE JUMPERS:  
 LINE SIDE, "A" SIDE OF COIL - RED ('R')  
 COMMON (GROUND OR NEUTRAL), "B" SIDE OF COIL - BLUE ('B')  
 ALL AC POWER WIRING:  
 A PHASE, LINE 1 - BLACK ('BK')  
 B PHASE, LINE 2 - RED ('R')  
 C PHASE, LINE 3 - BLUE ('B')  
 ALL WIRES ATTACHED TO LOAD BANK GROUND - GREEN ('G')  
 ALL LOAD JUMPERS AND STRAPPING - WHITE ('W')

1. UNIT MUST BE GROUNDED FOR OPERATORS SAFETY
2. DASHED LINES INDICATE WIRE NOT SUPPLIED BY SIMPLEX
3. LOAD WIRE #8 AVG., 150°C

THE INFORMATION HEREON IS THE PROPERTY OF SIMPLEX, INC., AND/OR ITS SUBSIDIARIES. WITHOUT WRITTEN PERMISSION ANY COPYING, TRANSMITTAL TO OTHERS AND USE EXCEPT THAT FOR WHICH IT IS LOANED IS PROHIBITED.

DISK 2/No. 2758	
<b>SIMPLEX</b> SPRINGFIELD, ILLINOIS	
DATE: 1/2/84	APPROVED BY: [Signature]
RESISTIVE LOAD BANK 400KW, 480V, 3Ø, 60HZ	NEPTUNE 400 LOAD SECTION
W.O. #16785-94-43	47862638